July 2010

Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: Resolution for CID 53, 334, 342, 370, 648, 649, 741

Date Submitted: 8th July, 2010

Source: Jaeseung Son

Company: Samsung Electronics Co.,LTD

Address: Dong Suwon P.O. Box 105, 416 Maetan-3dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-742 Korea

Voice:[82-31-279-5285], FAX: [82-31-279-5130], E-Mail:[js1007.son@samsung.com]

Re: []

Abstract: Comment and resolution

Purpose: Contribution to IEEE 802.15.7 TG-VLC

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

CID 53 (Subclause 5.3, page 5, line 23)

Comment

• The WPAN doesn't select an identifier, the Coordinator does.

Suggested Remedy

Change to "Each independent WPAN has an identifier, as defined in x.y.z."

- Accept
- Instruction to editor: change sentence from "Each independent WPAN selects a unique identifier." to "Each inde pendent WPAN has an identifier, as defined in 7.2.1.3 and 7.2 .1.5"

CID 334 (Subclause 6.4, page 39, line 22)

Comment

• The field length can't be variable.

Suggested Remedy

• Delete this figure and use a generic figure with boxes for SHR, Channel e stimation, PHR, PSDU and FCS. Don't put lengths in the figure, the lengt h of the fields is defined in the subclauses that define those fields.

- Figure and table is changed. Please refer document 15-10-0448-00-0007
- My suggestion is Accept.
- Instruction to editor: Please replace 6.4 PPDU with document 15–10– 0448–00–0007

CID 342 (Subclause 6.4.1, page 39)

Comment

• MCS for a given PHY TYPE not defined

Suggested Remedy

• We need to have a field added to the PPDU that indicates which MCS will be used for the packet body.

- MCS ID is inserted in PHY header. Please refer document 15– 10–0400–01–007
- So, my suggestion is Accept.
- Instruction to editor: Please replace 6.4 PPDU with document 15-10-0448-00-0007

CID 370 (Subclause 6.4.1.3, page 41, line 37)

Comment

 Why are specific PSDU frame lengths such as of 7 octets n ot allowed?

Suggested Remedy

• Remove constraints on allowed PSDU frame lengths

- Frame length values is deleted.
- My suggestion is Accept.
- Instruction to editor: Please replace 6.4 PPDU with document 15–10–0448–00–0007.

CID 648 (Subclause 7.2.1.1.6, page 133, line 10-14)

Comment

• This is procedural text in a descriptive clause.

Suggested Remedy

remove the paragraph

- Paragraph explains about table 68 in Destination Ad dressing Mode
- My suggestion is **Reject**.

CID 649 (Subclause 7.2.1.1.8, page 133, line 10-14)

Comment

• This is procedural text in a descriptive clause.

Suggested Remedy

remove the paragraph

- Paragraph explains about table 68 in Source Addres sing Mode subfield
- My suggestion is **Reject**.

CID 741 (Subclause 7.6.1, page 170, line 13)

Comment

• States that there is a single VLC MAC frame. This terminology is confusing, since subclause 7.2 defines the MAC frame formats of which t here are several unknown types. From Figure 104 it appears that the VLC Frame is below the physical layer.

Suggested Remedy

• Do not use this terminology to describe a framing structure on which MAC frames are transmitted.

- My suggestion is Accept.
- Instruction to editor: delete following sentence "The standard provides a single VLC MAC frame that can be configured for multiple modes."