September 2011

doc.: IEEE 15-11-0658-00-004g

Proposed Comment Resolution for CID # 188 (MR-O-QPSK PHY)

Michael Schmidt- ATMEL

September 20, 2011

IEEE P802.15 Wireless Personal Area Networks

Title:	Proposed Comment Resolution for CID $\#$ 188 (MR-O-QPSK PHY)
Date Submitted:	September 20, 2011
Source:	Michael Schmidt - Atmel (email: michael.schmidt@atmel.com)
Re:	Task Group 15.4g sponsor ballot comment resolution
Abstract:	Proposed comment resolution for CID #188 (MR-O-QPSK PHY)
Notice:	This document has been prepared to assist the IEEE P802.15.
	It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release:	The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

CID 188

Comment:

The commenter states: "There is no compelling reason why coherent detection is required for no spreading case. Pg 105, Line 18-20"

The commenter proposes the following: "Remove the description requiring coherent detection in this context"

Response:

Accept in principle.

Cont. CID 188

Response:

- According to P802.15.4g/D5, BDE is not specified for (1,1)-DSSS, see Table 147. This implies that non-coherent differential detection will not be supported for this mode.
- A receiver will require phase information in order to detect the information bits.
- Theoretical background information can be found in document IEEE 15-11-0639-00-004g.
- However, explicitly mandating coherent detection is not required in this context.

Proposed Change

At page 105, line 19 delete:

"For ${\sf N}=1$ (no spreading), coherent detection is required, employing a phase control loop based on the received chip samples."

At page 105, lines 42,43 delete:

"For (N,4)-DSSS, coherent detection is recommended, employing a phase control loop based on the maximum likelihood decision of the optimal codeword with respect to the (N,4) block code."