

July 2013

doc.: IEEE 802.15-13-0411-00-0thz_Literature Review

Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: Literature Review on Requirements for Wireless Data Centers

Date Submitted: 17 July 2013

Source: Thomas Kürner Company TU Braunschweig

Address Schleinitzstr. 22, D-38092 Braunschweig, Germany

Voice:+495313912416, FAX: +495313915192, E-Mail: t.kuerner@tu-bs.de

Re: IEEE 802.15-13-0130-01-0thz_Launching

Abstract: This documents follows the discussions at the previous IEEE 802 plenary on the application of wireless data centers when launching a study group on “Beam switchable wireless point-to-point 40/100 Gbps links”. The document summarizes some requirements on wireless data centers based on a literature study.

Purpose: Information of IEEE 802.15 IG THz

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Literature Review on Requirements for Wireless Data Centers

Thomas Kürner

TU Braunschweig

Introduction

- To the best knowledge of the author the first publication on wireless data centers has been made in 2008 [7].
- Since then a couple of papers on this topic have been published.
- This contribution briefly summarizes the key findings from a literature review focussing mainly on requirements for wireless data centers

Reasoning for introducing wireless links in data centers (from [1])

- Pure wired data centers are static and can not be reconfigured dynamically
- Cabling complexity
 - wastes much space
 - is hard to maintain
 - requires adequate cooling


General Requirements on Wireless Connectivity in Data Centers (from[7])

- High inter-node link capacity
- Reliability (predictable performance of links over time)
- Security isolation
- Scalability (interconnecting 10.000s of servers)
- Small form factor of networking components

Summary on Proposed Architectures

- Traditional DCN architectures are based on layered 2-tier (3tier-) architectures with core, (aggregation) and access layers [2]
- A couple of specific arrangements of the servers racks exploring the possibilities to introduce wireless links are proposed as well.
- In the following slides some of these proposals are presented


LOS and Indirect LOS Paths [4,7]




Hardware Components required for 3D Beamforming via Ceiling [4]

- Beamforming capabilities both in azimuth and elevation
- Ceiling reflectors (aluminium plates or other good reflecting materials)
- Electromagnetic absorbers on top of the racks to prevent local reflection/scattering around the antenna


Node Arrangements – Two Parallel Rows [2]




Node Arrangements – Hexagonal Shape [2]



Caley Data Center Design [6]



Intra-Rack Links



Inter-Rack Links

PHY/MAC Issues discussed in the literature (1/3)

- [2] uses the SC PHY of IEEE 802.15.3c due to low power requirements (assuming no non-LOS links are required)
- LOS 60 GHz links set-up at rack height provide stable performance [5]
- Assumption of stable channel conditions enable optimisation of beam-steering parameters during initialisation using look-up tables until reconfiguration [3]

PHY/MAC Issues discussed in the literature (2/3)

- Optimisation of Steered-beam table entries with respect to reachable neighbour nodes in order to avoid interference [3]
- Directional antennas can isolate links and enable spatial reuse [5]
- Results in [5] show that directional antennas are necessary to achieve high throughput over links above 1m

PHY/MAC Issues discussed in the literature (3/3)

- Efficient spectral re-use inherently reduces collision probability [3].
- In [5] it is shown that due to the low collision probability maximum TCP throughput could be increased by reducing unnecessary TCP overhead
- Discussion of using out-of-band signalling at lower frequencies [3].
- Channel Allocation and Scheduling aspects are discussed in detail in [8,9]

List of References (1/2)

- [1] Kaishun Wu, „Rethinking the architecture design of data center networks”, Front. Comp. Science, Review Article, 2012 (9 pages)
- [2] H. Vardhan, Wireless Data Center with Millimeter Wave Network, Proc. IEEE Globecom 2010
- [3] Katayama Y, Takano K, Kohda Y, Ohba N, Nakano, “Wireless data center networking with steered-beam mmwave links”, in: Proceeding of 2011 IEEE Wireless Communications and Networking Conference. 2011, pp. 2179–2184
- [4] Zhang W et. al, „3D beamforming for wireless data centers”, in Proceedings of the 10th ACM Workshop on Hot Topics in Networks. 2011
- [5] D. Halperin et. al, „Augmenting Data Center Networks with Multi-Gigabit Wireless Links“, SIGCOMM 2011
- [6] „On the feasibility of Completely Wireless Data Centers“, <http://www.cs.cornell.edu/courses/cs6452/2012sp/papers/cayley.pdf>
- [7] K. Ramchadran, „60 GHz Data-Center Networking: Wireless Worry less?“, 2008

List of References (2/2)

- [8] Y. Cui et al., „ Channel Allocation in Wireless Data Center Networks“, IEEE INFOCOMM 2011
- [9] Y. Cui et al., „ Wireless Link Scheduling for Data Center Networks“, ICUIMC'11, February 21-23, 2011, Seoul, Korea