

Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: [PHY proposal for existing Sub 1-GHz bands in 15.4]

Date Submitted: [15 May, 2016]

Source: [Kunal Shah] Company [Silver Spring Networks]

[] Company []

Address []

Voice: [], E-Mail:[kshah @ silverspringnet.com]

Re: []

Abstract: [PHY proposal to support Sub 1-GHz band]

Purpose: [To be considered in the PHY amendment as part of 802.15.4v]

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Background

- **Scope of the project:**

“This amendment defines changes to the IEEE Std 802.15.4-2015 PHY clauses enabling the use of the 870-876 MHz & 915-921 MHz bands in Europe, the 902-928 MHz band in Mexico, the 902-907.5 MHz & 915-928 MHz bands in Brazil, the 915-928 MHz band in Australia/ New Zealand and Asian regional frequency bands that are not in IEEE Std 802.15.4-2015. This amendment also changes the channel parameters for the 470-510 MHz band in China and the 863-870 MHz band in Europe for SUN PHYs, and aligns these channel parameters with regional requirements. The amendment includes channel access and/or timing changes to the MAC necessary for conformance to regional requirements for these bands.”

Purpose and Objective

- PHY parameters as specified in 15.4 can not be operational per regional requirements
- Specify operational PHY parameters for existing 15.4 regions

Technical Details (Chinese Band)


Table 243—SUN FSK modulation and channel parameters^a (continued)

4) 使用频率：470-510MHz,

发射功率限值：50mW(e.r.p)

2.占用带宽：不大于200kHz

Frequency band (MHz)	Parameter	Operating mode #1	Operating mode #2	Operating mode #3
470–510	Data rate (kb/s)	50	100	200
	Modulation	2-FSK	2-FSK	4-FSK
	Modulation index	1.0	1.0	0.33
	Channel spacing (kHz)	200	400	400
779–787	Data rate (kb/s)	50	100	200
	Modulation	2-FSK	2-FSK	4-FSK
	Modulation index	1.0	1.0	0.33
	Channel spacing (kHz)	200	400	400
863–870	Data rate (kb/s)	50	100	200
	Modulation	2-FSK	2-FSK	4-FSK
	Modulation index	1.0	1.0	0.33
	Channel spacing (kHz)	200	400	400



Technical Details (European Band)

Table 243—SUN FSK modulation and channel parameters^a (continued)

Frequency band (MHz)	Parameter	Operating mode #1	Operating mode #2	Operating mode #3		
470–510	Data rate (kb/s)	50	100	200		
	Modulation	2-FSK	2-FSK	4-FSK		
	Modulation index	1.0	1.0	0.33		
	Channel spacing (kHz)	200	400	400		
779–787	Data rate (kb/s)	50	100	200		
	Modulation	2-FSK	2-FSK	4-FSK		
	Modulation index	1	863-870 MHz (notes 3 and 4)	25 mW e.r.p.	≤ 0.1% duty cycle or LBT (notes 1 and 5)	≤ 100 kHz for 47 or more channels (note 2)
	Channel spacing (kHz)	2				
863–870	Data rate (kb/s)	50	100	200		
	Modulation	2-FSK	2-FSK	4-FSK		
	Modulation index	1.0	1.0	0.33		
	Channel spacing (kHz)	200	400	400		

Modulation and Channel Parameters (SUN FSK)

Frequency band (MHz)	Parameter	Operating Mode #1	Operating Mode #2	Operating Mode #3
470-510 (China)	Data Rate (kbps)	50	100	150
	Modulation	2-FSK	2-FSK	2-FSK
	Modulation Index	1.0	0.5	0.5
	Channel spacing (kHz)	200	200	200
863 - 870 (Europe)	Data Rate (kbps)	50	100	150
	Modulation	2-FSK	2-FSK	2-FSK
	Modulation Index	0.5	0.5	0.5
	Channel spacing (kHz)*	100	200	200

* Channel spacing requirements per ERC Rec 70-03 [CEPT]

Modulation and Channel Parameters for Chinese and European band

Modulation	Support for OFDM Option 4 as per sub-clause 21 (SUN OFDM PHY)
SUN OFDM Optional Mode	Data rates supported (kb/s): 50, 100, 150, 200, 300 Channel Spacing (kHz): 200 Nominal bandwidth (kHz): 156

Modulation	Support for SUN O-QPSK
SUN O-QPSK Optional Mode	Rate Mode: 0,1,2,3 Data rates supported (kb/s): 6.25, 12.5, 25, 50 Channel Spacing (kHz): 200 Chip rate (kchip/s): 100

Modulation and Channel Parameters (Contd..)

- Summary
 - SUN FSK (Mandatory Mode)
 - 50 kbps (Mandatory data rate)
 - 100 kbps and 150 kbps (Optional data rate)
 - SUN OFDM 4 (Optional Mode)
 - 50, 100, 150, 200, and 300 kbps (Optional data rates)
 - SUN O-QPSK (Optional Mode)
 - 6.25, 12.5, 25 and 50 kbps

- All additional PHY parameters shall be as per existing SUN FSK, SUN OFDM and SUN O-QPSK

Reference

- IEEE Std. 802.15.4-2015, Part 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs)
- IEEE Std. 802.15.4g-2012, Part 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs) - Amendment 3: Physical Layer (PHY) Specifications for Low-Data-Rate, Wireless, Smart Metering Utility Networks, March 2012.
 - <https://standards.ieee.org/findstds/standard/802.15.4g-2012.html>