

Project: IEEE P802.15 Working Group for Wireless Personal Area Networks (WPANs)

Submission Title: Ranging Accuracy Evaluation under TG6ma Communication Scenarios

Date Submitted: May 14th, 2025

Source: Daisuke Anzai, Yuhei Oguri, Shunsuke Ishiguro, Takumi Kobayashi

Company: Osaka Metropolitan University, Japan

Address: Gokiso-cho, Showa-ku, Nagoya, 466-8555, Japan

Voice: +81-52-735-5389, **FAX:** +81-52-735-5389, **E-Mail:** d.anzai@omu.ac.jp

Re: In response to call for technical contributions

Abstract: This provides a preliminary investigation of the effect of interference cancellation on UWB ranging accuracy under multiple BAN coexistence situations, and some simulation results are discussed.

Purpose: Material for discussion in P802.15.6a TG corresponding to comments in EC Meeting

Notice: This document has been prepared to assist the IEEE P802.15. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release: The contributor acknowledges and accepts that this contribution becomes the property of IEEE and may be made publicly available by P802.15.

Ranging Accuracy Evaluation under TG6ma Communication Scenarios


Daisuke Anzai, Yuhei Oguri, Shunsuke Ishiguro,
Takumi Kobayashi
Nagoya Institute of Technology (NIT)

Introduction

- Ranging is a key issue in various kinds of UWB applications, including IEEE 802.15.6ma, 4ab, and 4z
- UWB techniques have the potential to achieve high accuracy in supporting important applications in HBAN and VBAN
- It is important to discuss the ranging accuracy under multiple BAN coexistence situations under the BAN channel models


UWB ranging in CFP

- It is more realistic that ranging is performed in contention free period (CFP), which results in the realization of both data transmission and ranging in the same period



Propagation model in a hospital room^[1]

$$\text{PDP model : } h(t) = \sum_{l=0}^{L-1} a_l \exp(j\varphi_l) \delta(t - t_l)$$



Parameters		Values
a_l	γ_0	-4.60 dB
	Γ	59.7
t_l	$1/\lambda$	1.85 ns
L	$\bar{L}$	20

Amplitude

$$10\log_{10}|a_l|^2 = \gamma_0 + 10\log_{10}\left(\exp\left(-\frac{t_l}{\Gamma}\right)\right)$$

Path arrival time

$$p(t_l|t_{l-1}) = \lambda \exp(-\lambda(t_l - t_{l-1}))$$

Number of the arrival paths

$$p(L) = \frac{\bar{L}^L \exp(-\bar{L})}{L!}$$

a_l : Path amplitude

t_l : Path arrival time

φ_l : Path phase

$\delta(t)$: Dirac function



Γ : Exponential decay

γ_0 : Rician factor

L : Number of the arrival paths

[1]: K. Takizawa, T. Aoyagi, H. -B. Li, J. -i. Takada, T. Kobayashi and R. Kohno, "Path loss and power delay profile channel models for wireless body area networks," 2009 IEEE Antennas and Propagation Society International Symposium, North Charleston, SC, USA, 2009, pp. 1-4.

Ranging accuracy evaluation (SNR: 20 dB)




Technical requirement

Achieve a ranging accuracy of below 0.3 m

	0.5 GHz	1.0 GHz	2.0 GHz
RMSE [m]	0.754814	0.563771	0.044247

The sampling rate of 2 GHz satisfied the requirement

Ranging accuracy evaluation (SNR: 40 dB)



Fading: **flat**


Sampling frequency at receiver: 0.5, 1, 2 GHz

Cross-correlation detection

AWGN: **SNR of more than 40 dB**

d_{TR} = Determined by uniform random numbers of 3-4 m

d_{IR} : Determined by uniform random numbers of 1-6 m each





Technical requirement

Achieve a ranging accuracy of below 0.3 m

	0.5 GHz	1.0 GHz	2.0 GHz
RMSE [m]	0.186388	0.083677	0.044051

All sampling rates satisfied the requirement under clear channel condition

Ranging accuracy evaluation under coexistence scenario






No performance degradation was confirmed
with M-sequence-based interference mitigation

Sampling frequency: 1 GHz



Coexistence of up to five interference nodes

M-sequence-based interference mitigation

UWB antenna modeling





Simulation results



$$PL \text{ [dB]} = PL_0 + 10n \log_{10} \left(\frac{d}{d_0} \right)$$

Parameters	PL_0 [dB] ($d=1000$ mm)	n	RMSE [dB]
Rx1 @4GHz	37.6	7.45	4.41
Rx2 @4GHz	50.9	6.00	2.07
Rx1 @8GHz	49.0	5.39	2.05
Rx2 @8GHz	59.3	2.66	1.43

Simulation results



References

1. D. Anzai, I. Balasingham, G. Fischer, J. Wang, “Reliable and High-Speed Implant Ultra-Wideband Communications with Transmit–Receive Diversity,” EAI/Springer Innovations in Communication and Computing, pp. 27-32, March 2020.
2. Y. Shimizu, D. Anzai, R. C-Santiago, P. A. Floor, I. Balasingham, and J. Wang, “Performance evaluation of an ultra-wideband transmit diversity in a living animal experiment” IEEE Trans. Microw. Theory Tech., vol. 65, no. 7, pp. 2596-2606, July 2017.
3. D. Anzai, K. Katsu, R. Chavez-Santiago, Q. Wang, D. Plettemeier, J. Wang, and I. Balasingham, “Experimental evaluation of implant UWB-IR transmission with living animal for body area networks,” IEEE Trans. Microw. Theory Tech., vol. 62, no. 1, pp. 183-192, Jan. 2014.
4. J. Shi, D. Anzai, and J. Wang, “Channel modeling and performance analysis of diversity reception for implant UWB wireless link,” IEICE Trans. Commun., no. E95-B, vol. 10, pp. 3197-3205, Oct. 2012.