

1
2

IEEE P802.18
Radio Regulatory Technical Advisory Group (RR-TAG)

Draft Response Czech Spectrum Strategy Consultation

Date: 2023-08-25

Author(s):

Name	Company	Address	Phone	email
Benjamin Rolfe	BCA			ben.rolfe@ieee.org
Dries Neiryndk	Ultra-Radio			dries.neiryndk@ultra-radio.com
Edward Au	Huawei			edward.ks.au@gmail.com
Clint Powell	HID Global			cpowell@ieee.org
Hassan Yaghoobi	Intel			Hassan.yaghoobi@intel.com
Claudio da Silva	Meta			claudiodasilva@meta.com
David Goodall	Morse Micro			dave@morsemicro.com
David Halasz	Morse Micro			dave.halasz@ieee.org
Dorothy Stanley	HP Enterprise			dstanley@ieee.org

3

4 This contribution proposed a response to:

Czech Republic Czech Telecommunications Office (CTU)'s call for comments on the update of the Radio Spectrum Management Strategy consultation. See <https://www.ctu.eu/call-comments-update-radio-spectrum-management-strategy>.

Notice: This document has been prepared to assist IEEE 802.18. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

5
6 Electronic filing

August 21, 2023

7
8 Re: Czech Republic CTU's call for comments on the update of the Radio Spectrum Management
9 Strategy update.

10
11 Dear Chairman, CTU, Radio Department, Policy and Strategy Unit,

12
13 IEEE 802 LAN/MAN Standards Committee (LMSC) thanks Czech Republic Czech
14 Telecommunications Office (CTU) for providing this opportunity to participate in the process of
15 updating the current version of the Radio Spectrum Management Strategy ("report").

16
17 IEEE 802 LMSC is a leading consensus-based industry standards body, producing standards for
18 wireless networking devices, including wireless local area networks ("WLANs"), wireless
19 specialty networks ("WSNs"), wireless metropolitan area networks ("Wireless MANs"), and
20 wireless regional area networks ("WRANs"). We also produce standards for wired Ethernet
21 networks, and technologies produced by implementers of our standards are critical for all
22 networked applications today.

23
24 IEEE 802 LMSC is a committee of the IEEE Standards Association and Technical Activities, two
25 of the Major Organizational Units of the Institute of Electrical and Electronics Engineers (IEEE).
26 IEEE has about 400,000 members in over 160 countries. IEEE's core purpose is to foster
27 technological innovation and excellence for the benefit of humanity. In submitting this document,
28 IEEE 802 LMSC acknowledges and respects that other components of IEEE Organizational Units
29 may have perspectives that differ from, or compete with, those of IEEE 802 LMSC. Therefore,
30 this submission should not be construed as representing the views of IEEE as a whole¹.

31
32 Please find below the comments of IEEE 802 LMSC to selected sections of the report.

33 34 **Updates on UWB in Section 6.4.4.2: Short-range devices (SRD)**

35
36 Section 6.4.4.2 of the report states: "*Applications using the ultra-wideband technology (UWB) met*
37 *the expectations only to a very limited extent and tend to be used in industrial applications (cable*
38 *detection, identification of vehicles and surveillance applications, support of safety in industry,*
39 *etc.)". IEEE 802 LMSC would like to inform the CTU that the application and deployment of*
40 *UWB technology has changed dramatically since the publication of the report. Today, UWB*
41 *technology based on IEEE Std 802.15.4 is included in mass market consumer devices, including*
42 *smartphones, vehicles, and consumer accessories. UWB is a key technology in indoor location*
43 *tracking, material sensing, and other industrial applications. Growth into consumer products,*
44 *however, is a significant change.*

45 46 **Current and future state of IEEE 802.15.4 UWB**

47
48 IEEE 802.15 standards specify UWB technology operation. IEEE Std 802.15.4-2020 [1] and IEEE
49 Std 802.15.4z-2020 [2] are standards for precision ranging that support data communication,
50 location discovery, and device ranging. The standards support operation in many frequency ranges
51 including sub-1 GHz bands and 3.1 GHz to 10.6 GHz bands [3] and are increasingly used in many

¹ This document solely represents the views of IEEE 802 LMSC and does not necessarily represent a position of either the IEEE or the IEEE Standards Association.

52 high value applications. The capability of IEEE Std 802.15.4z-2020 to support secure ranging has
53 led to a renewed interest in UWB from industry. The automotive industry was the driving force
54 behind IEEE Std 802.15.4z-2020 and the first to include UWB in consumer products. Mobile
55 handset makers have followed closely. This is generating significant economic and social value,
56 attracting further interest in developing a robust and diverse industry ecosystem. For example, the
57 UWB Alliance supports members in many application areas, including but not limited to
58 agriculture, sensing, and radar; the FiRa Consortium is focused on precise (fine) ranging
59 applications and localization; OmLox is supporting industrial localization; the Car Connectivity
60 Consortium has been focused on automotive uses; while the Connectivity Standards Alliance is
61 focused on secure premises access for, but not limited to corporate, hospitality, university, single-
62 family homes, and multi-family homes. There is cooperation among these organizations to support
63 the broad needs of the industry in complimentary ways.

64
65 The IEEE 802.15.4ab task group [4] is developing the next generation of UWB standard based on
66 industry needs to fuel the next round of innovative products. The IEEE P802.15.4ab project is built
67 on IEEE Std 802.15.4z-2020 which is capable of using both the 6 GHz and 7 GHz frequency
68 bands. New developments supported by the project include features to improve link budget and/or
69 reduce air-time, sensing capabilities to support presence detection and environment mapping,
70 improved accuracy, precision and reliability for high-integrity ranging, interference mitigation
71 techniques to support greater device density and higher traffic use cases and to provide improved
72 coexistence in the presence of other services in support of different regulatory requirements.
73 Additional mechanisms are being defined to reduce complexity and power consumption, and to
74 enhance support for ultra-low energy and low latency streaming, while ensuring compatibility with
75 the deployed base of products.

76 77 *Expanded applications and massive growth*

78
79 It can be noted that the uses which the CTU identified in 2015 were, then and still today, critically
80 important uses. UWB is still used for location tracking and material sensing in industrial
81 environments extensively. The market has significantly expanded. Following completion of ECC
82 Report 278 and IEEE Std 802.15.4z-2020, UWB has become ubiquitous and there are lots of active
83 UWB development and deployments. For example, UWB is now used to secure passive keyless
84 entry systems in many vehicles and for premises access. Mobile phone manufacturers have also
85 been integrating UWB in their smart phones.

86
87 Sensing based upon UWB is another area of explosive growth. The ultra-low transmit power (at
88 or below unintentional emissions limits) and very high dynamic response of impulse radio-UWB
89 (IR-UWB) enables precise, fast, and accurate sensing for uses such as presence detection of
90 children left in vehicles.

91
92 As another example of current market trends, UWB is emerging as a leading technology for ultra-
93 low power, ultra-low latency moderate data rate communications such as real time audio and real-
94 time ultra-low latency human interface devices for gaming.

95
96 In summary, while it may have appeared in 2015 that UWB had not lived up to original
97 expectations, presently UWB deployments are numbering over a billion devices and are growing
98 exponentially [5]. The UWB adoption timeline is consistent with that of the other popular license
99 exempt technologies from first rulemaking to mass market adoption.

100

101 **It is an appropriate time to develop a strategic plan for UWB**

102
103 Given the increasing importance of UWB, IEEE 802 LMSC would like to encourage the CTU to
104 include a strategy for UWB development in its radio spectrum management strategy.

105
106 Within CEPT, ECC Report 327 led to an update of ECC Decision (06)04 last year, removing the
107 prohibition on fixed outdoor devices, simplifying the use of UWB in vehicular applications and
108 enhancing the transmit power of indoor devices. IEEE 802 LMSC respectfully ask the CTU to
109 include these measures in the Czech Republic's national regulations. Harmonization of regulations
110 has many benefits, both technical and economic. In addition, CEPT ECC SE24 is beginning to
111 revisit the UWB regulations in the 8.5 GHz to 10.6 GHz bands.

112
113 Furthermore, as the number and variety of applications of IEEE 802.15.4 UWB devices continue
114 to grow, radio spectrum policies and spectrum regulations can help combat climate change by
115 creating conditions conducive to lowering power usage. For example, with the constraint of -41.3
116 dBm/1 MHz power spectral density, or in other terms, 37 nJ/ms, the IEEE 802.15.4 UWB radios
117 cause very little or no interference to other users of the same spectrum (e.g., there are defined
118 restrictions for UWB radios to operate from 3.1 GHz to 10.6 GHz bands), but the IEEE 802.15.4
119 radios themselves may become blocked by strong nearby signals. While regulations do not protect
120 IEEE 802.15.4 radios from interference, spectrum policies can keep parts of the spectrum suitable
121 for energy efficient low power device use.

122
123 Additional information that the CTU may find helpful in updating its spectrum strategy, including
124 potential updates to current rules for UWB, can be found in the references [6] [7].

125
126 **Updates on IEEE 802.11/Wi-Fi to Section 6.4.4.1: WiFi radio access networks**

127
128 **IEEE 802.11 technologies provide significant economic value**

129
130 IEEE 802.11 technologies are integral to the modern communications infrastructure and vital for
131 sustaining social and economic progress of citizens, enterprises, and governments in the Czech
132 Republic and worldwide.

133
134 IEEE 802.11 technologies directly support quality communication services, spur economic
135 development, and foster innovation, benefiting established and developing communities alike. For
136 example, Wi-Fi technology, which is based on the IEEE 802.11 standard, serves as an important
137 platform for offering free internet access, fostering educational and business opportunities in
138 underserved communities. IEEE 802.11 technologies are a key enabler of emerging applications
139 such as augmented and virtual reality (AR/VR), industrial IoT, and dense deployment scenarios
140 such as stadiums. With a global device estimate of 18 billion and an annual addition of 4 billion
141 devices [8], IEEE 802.11 technologies drive economic growth and innovation. As shown in [9],
142 the number of Wi-Fi hotspots was expected to grow fourfold from 2018 to 2023, and have about
143 628 million public Wi-Fi hotspots by the end of 2023. As shown in an industry consortia report
144 [10], Wi-Fi contributes USD \$458 billion in European Union's economic value in 2021, and the
145 economic value is expected to increase to USD \$637 billion by 2025.

Current and future state of IEEE 802.11

Today, Wi-Fi networks based on IEEE 802.11 standards are found in residential, office, and industrial environments, in public and private settings. Users in an array of industries rely on these cost effective, energy efficient technologies. Each new generation of IEEE 802.11 technologies continues to improve efficiency, reliability, latency, throughput, and determinism. IEEE 802.11 standards support operation in several frequency bands, including the sub-1 GHz, 2.4 GHz, 5 GHz, 6 GHz (5925 MHz to 7125 MHz), and 60 GHz (57 GHz to 71 GHz) bands, with significant global deployments.

IEEE 802.11 technologies include a number of mechanisms that lead to efficient and sustainable utilization of the radio spectrum. IEEE 802.11 technologies, for example, adopt a Listen-Before-Talk (LBT)-based interference avoidance procedure and incorporate power saving mechanisms such as Target Wake Time (TWT). As discussed below, the new generation of IEEE 802.11 technologies, currently under development in the IEEE P802.11be amendment, will continue to improve performance and enhance spectrum coexistence capacities.

Of note, the IEEE Std 802.11ax-2021 [11] standard supports operation in the upper 6 GHz band (6425 MHz to 7125 MHz), and products based on this standard are seeing significant adoption where regulatory rules permit deployment [12]. The significance of unlocking the upper 6 GHz band for Wi-Fi radio access networks cannot be overstated, as access to larger, contiguous bandwidths in the 6 GHz band reduces the potential for harmful interference [13] and allows for IEEE 802.11 technologies to support more effectively emerging delay-sensitive residential, enterprise, and industrial applications. A new generation of IEEE 802.11 technologies, currently under development in the IEEE P802.11be amendment, will continue to enhance coexistence strategies and provide even more effective spectrum sharing and sustainable utilization in these bands. Moreover, the Wi-Fi industry is taking the lead in specifying coexistence strategies for bands with incumbent users, such as automated frequency coordination [14], [15], [16] and other coexistence mechanisms supported by different regulatory methods in the 6 GHz band [17].

The agriculture industry is one of the most important sectors of the Czech Republic's economy. The IEEE 802.11ah-2016 standard [18], known as Wi-Fi HaLow in the marketplace, is an amendment to the IEEE 802.11 standard that specifies mechanisms for operation of Wi-Fi in sub 1 GHz bands. It was developed with sensor and IoT networks in mind and agriculture is one of the potential applications [19]. IEEE 802.11ah-2016 standard includes an access point (AP) Power Save Mode. In this mode, the AP can signal to non-AP devices in the network that it is going to be in a "doze mode" for a period of time. By negotiating the length of the doze mode in advance, the AP and the non-AP devices can both conserve energy. This amendment introduced many features to increase energy efficiency. These include reducing overhead and relaxing timing for energy limited clients that typically operate from a coin cell. It also introduced TWT, which allows long sleeping devices to negotiate a time for the device to be active. This enables optimizing power consumption per device.

Suggested modifications to Section 6.4.4.1. WiFi radio access networks

Note: The text that follows suggests modifications to Section 6.4.4.1 as it appears in the report. The suggested modifications describe what is proposed to be changed by using ~~strikethrough~~ (to remove text from the current Radio Spectrum Management Strategy) and underscore (to add new material).

197 *Note: IEEE 802 LMSC respectfully asks the CTU to consider replacing “WiFi” with “Wi-Fi”*
198 *throughout the report.*

199

200 6.4.4.1. WiFi radio access networks

201

202 From economic point of view, the use of WiFi technology is among the most important ones. WiFi
203 technology is used for wireless access networks as well as for offloading of 3G/4G/5G data traffic
204 terminals (data off-loading¹⁰⁹). Bands 2400 – 2483.5 MHz (frequency band 2.4 GHz), and 5150 –
205 5350 MHz and 5470 – 5725 MHz (frequency band of 5 GHz), and 5945 – 6425 MHz (frequency
206 band 6 GHz) are harmonised in Europe for WiFi technology¹⁴⁴ and are used by computers, tablet
207 PCs, smart phones and other devices designed for connection to public and private networks. It is
208 estimated¹⁴⁵ that WiFi connection is used by 75 % of the users of smart phones. In most regions
209 of the world WiFi is understood as a key component of development of Internet connection.
210 Standard IEEE 802.11n practically enables speed over 100 Mbit/s, and standards IEEE 802.11ac
211 and IEEE 802.11ax enable speeds of over 1000 Mbit/s and 802.11ae gigabit speed.

212

213 The IEEE Std 802.11ax-2021 [11] standard supports operation in the 6425 MHz to 7125 MHz
214 bands with channel bandwidth of up to 160 MHz, and products based on this standard are seeing
215 significant adoption where regulatory rules permit deployment [12]. IEEE 802 technologies are
216 designed not to cause interference with other users in these bands. The Wi-Fi industry is taking
217 the lead in specifying a number of co-existence strategies for bands with incumbent users, such as
218 automated frequency coordination [14], [15], [16].

219

220 The new generation of IEEE 802.11 technologies, currently under development in the IEEE
221 P802.11be amendment, will continue to improve performance and enhance spectrum coexistence
222 capacities. To achieve the targeted performance improvements, IEEE P802.11be introduces
223 advanced features including channel bandwidths of up to 320 MHz, multiple resource units to a
224 single station, multi-link operation, enhanced quality of service (QoS), improved TWT (for
225 improved battery life for IoT or other applications), and improved punctured
226 transmission/subchannels to accommodate coexistence with incumbents more effectively and
227 efficiently. The P802.11be amendment currently supports carrier frequency operation between
228 1000 MHz and 7125 MHz with extension to 7250 MHz under consideration.

229

230 For the Wi-Fi 6 generation of products, IEEE 802.11ax introduced a trigger mechanism where the
231 Wi-Fi AP can schedule uplink transmissions of a client, enabling predictability of access.
232 Moreover, if a Wi-Fi 6 AP knows the QoS (throughput, latency) requirement of a client, the AP
233 can schedule the clients accordingly. IEEE 802.11be, known as Wi-Fi 7 in the marketplace, further
234 enhances the ability to control the medium (e.g., through restricted target wake time service
235 periods, a.k.a. rTWT, advertised in Beacon frames). These scheduling mechanisms introduced in
236 IEEE 802.11ax and IEEE 802.11be work well to deliver predictable QoS in environments where
237 the spectrum environment is controlled by a network manager, e.g., in industrial and
238 manufacturing sites and stadiums. Additionally, IEEE 802.11be defines multi-link operation to
239 further support high determinism and QoS and wide channel bandwidths up to 320 MHz to support
240 increased throughput and capacity.

241

242 The related standards IEEE 802.11ad and IEEE 802.11ay (WiGig), approved in 2013 and 2021,
243 respectively, will enable multi-gigabit communication at short distance in the bands 57 – 7166
244 GHz. In addition, the IEEE 802.11ah (HaLow) standard provides connectivity to beyond 1 km for
245 low power, long range IoT devices in the sub-1 GHz band.

246

247 The potential of WiFi is based on the possibility of license-free operation and on continuous
 248 innovation – relative to the first specification of devices with speed 11 Mbit/s today's standards
 249 have exceeded the achievable speed almost by ~~two~~ three orders.

250

251 Popularity and development of WiFi will be also supported by the development of 4G and 5G
 252 networks which, in a certain phase of development, envisage offloading of the traffic by means of
 253 WiFi. WiFi networks ~~could become~~ are an integral part of mobile communication networks (e.g.,
 254 by means of the WiFi hotspots). ~~The decision on the expansion, if any, of additional frequencies~~
 255 ~~for mobile access networks in the frequency band of 5 GHz will be made by the international~~
 256 ~~conference WRC-15. In this context, the European Commission issued mandate to CEPT in 2013~~
 257 ~~to prepare a study of utilisation of the sections 5350 – 5470 MHz and 5725 – 5925 MHz by FWA~~
 258 ~~networks designated for provision of broadband services of electronic communications~~¹⁴⁶.

259



260

261 Figure No. 3 – Current and possible future configuration of the band of 5 GHz for FWA/WiFi

262

263 Figure No. 3a – Current and possible future configuration of the band of 6 GHz for FWA/WiFi

264

265 The expansion of bands pro FWA is conditional upon compatibility with other civil and non-civil
 266 use of the bands, in particular the radiolocation service, scientific services¹⁴⁷ and intelligent
 267 transport systems ITS¹⁴⁸ which are or will be important for ensuring security, fluency and economy
 268 of road traffic. The expansion of the bands would enable homogenous use of the spectrum by
 269 BWA/FWA/WiFi systems using channel width up to ~~320~~160 MHz which enable gigabit data
 270 throughput for enterprise and dense usages of innovative applications such as AR/VR. In some
 271 countries, the frequency band 5.725 – 5.825 GHz is now used¹⁴⁹ under the so-called light license
 272 usually in rural areas for wireless access. The preliminary internal analysis of the Office prepared
 273 according to the measurement results suggests compatibility of the existing ITS systems with
 274 BWA/FWA/WiFi systems. In the frequency band of 5350 – 5470 MHz the facilitation of mutual
 275 coexistence is significantly more complicated and it would require sophisticated procedures
 276 preventing mutual interference (e.g., geo-location databases).

277

278 *Consequences of utilisation of the spectrum by WiFi networks:* In both frequency bands of 2.4
 279 GHz and 5 GHz designated for the operation of WiFi networks there have been cases of mutual
 280 local interference of the networks and other signs indicating quite high load on the band. In a part
 281 of the 5GHz band designated for the operation of outdoor networks there are instances of
 282 interference with meteorological radars due to WiFi operators' failure to comply with the operating
 283 conditions. Since this phenomenon has very adverse implications for the quality of the services
 284 using the information from the meteorological radars the problem is dealt with both on
 285 international level and on national level (see Article 3.6).

286

287 **Conclusion**

288

289 IEEE 802 LMSC thanks the CTU for the opportunity to provide this submission. We encourage
290 the CTU in future version of the Radio Spectrum Management Strategy to take into account the
291 latest development of IEEE 802.11 and IEEE 802.15 technologies and consider a strategic plan
292 for UWB.

293

294 Respectfully submitted

295

296 By: /ss/.

297 Paul Nikolich

298 IEEE 802 LAN/MAN Standards Committee Chairman

299 em: p.nikolich@ieee.org

300

301 References:

302

303 [1] "IEEE Standard for Low-Rate Wireless Networks," in IEEE Std 802.15.4-2020 (Revision
304 of IEEE Std 802.15.4-2015), vol., no., pp.1-800, 23 July 2020, doi:
305 10.1109/IEEESTD.2020.9144691.

306 [2] "IEEE Standard for Low-Rate Wireless Networks--Amendment 1: Enhanced Ultra
307 Wideband (UWB) Physical Layers (PHYs) and Associated Ranging Techniques," in
308 *IEEE Std 802.15.4z-2020* (Amendment to IEEE Std 802.15.4-2020), vol., no., pp.1-174,
309 25 Aug. 2020, doi: 10.1109/IEEESTD.2020.9179124.

310 [3] IEEE 802.18 Wireless Standards Table of Frequency Ranges, Sept. 2022. [Available online](#)
311 [accessed: 25 August 2023]

312 [4] IEEE P802.15.4ab. [Available online](#) [accessed: 25 August 2023]

313 [5] FiRa Consortium, "Unleashing the Potential of UWB: Regulatory Considerations," Dec.
314 2022. [Available online](#) [accessed: 25 August 2023]

315 [6] FiRa Consortium, "Spectrum Position Statement," Jul. 2023. [Available online](#) [accessed: 25
316 August 2023]

317 [7] Car Connectivity Consortium. "UWB Spectrum Regulatory Position, Car Connectivity
318 Consortium Digital Key – The Future of Vehicle Access," Dec. 2022, [Available online](#)
319 [accessed: 25 August 2023]

320 [8] Wi-Fi Alliance: Value of Wi-Fi. [Available online](#) [accessed: 25 August 2023].

321 [9] Cisco Annual Internet Report (2018–2023) White Paper. [Available online](#) [accessed: 25
322 August 2023]

323 [10] Wi-Fi Alliance: Global Value of Wi-Fi. [Available online](#) [accessed: 25 August 2023]

324 [11] "IEEE Standard for Information Technology - Telecommunications and Information
325 Exchange between Systems Local and Metropolitan Area Networks - Specific Requirements
326 Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY)
327 Specifications Amendment 1: Enhancements for High-Efficiency WLAN," in IEEE Std
328 802.11ax-2021 (Amendment to IEEE Std 802.11-2020), pp.1-767, 19 May 2021, doi:
329 10.1109/IEEESTD.2021.9442429.

330 [12] Wi-Fi Alliance: Wi-Fi 6E momentum underscores need for entire 6 GHz band, November
331 2022. [Available online](#) [accessed: 25 August 2023].

332 [13] CEPT: Section 6.2.6, ECC Report 302 - Sharing and compatibility studies related to Wireless
333 Access Systems including Radio Local Area Networks (WAS/RLAN) in the frequency band
334 5925-6425 MHz, May 2019. [Available online](#) [accessed: 25 August 2023].

335 [14] Dynamic frequency coalition: Automated frequency coordination - an established tool for
336 modern spectrum management, March 2019. [Available online](#) [accessed: 25 August 2023].

- 337 [15] Intel: Spectrum Sharing Using Automated Frequency Coordination, [Available online](#) [25
338 August 2023].
- 339 [16] Wi-Fi Alliance: 6 GHz AFC resources. [Available online](#) [accessed: 25 August 2023]
- 340 [17] UK Ofcom: Update on the upper 6 GHz band. [Available online](#) [accessed: 25 August 2023]
- 341 [18] IEEE Standard for Information technology—Telecommunications and information exchange
342 between systems - Local and metropolitan area networks—Specific requirements - Part 11:
343 Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications
344 Amendment 2: Sub 1 GHz License Exempt Operation, in IEEE Std 802.11ah-2016
345 (Amendment to IEEE Std 802.11-2016, as amended by IEEE Std 802.11ai-2016), vol., no.,
346 pp.1-594, 5 May 2017, doi: 10.1109/IEEESTD.2017.7920364.
- 347 [19] Wi-Fi Alliance: The future of farming: Testing the rural range of Wi-Fi CERTIFIED
348 HaLow™. [Available online](#) [accessed: 25 August 2023]